

1 piece JT 380 eTurner AKKU-electric turning-machine on crawler chassis



Kits:

- Rental lane assistant with cruise control
- Automatic driving with adjustable motor power
- 3 sensors for rent detection
- 6 different driving programs can be preselected on the remote control

Options:

1 piece battery charger

High Frequency Charger 400 V~/ 16 Amps
Output: 80 V = 120 Ah
Protection class IP 54

1 piece quick-change lead-acid battery

80 V/ 750 AH
Version with armor plates
incl. quick-release frame and
Cover

Specifications

Windrow width max.	3.80 m
Rent amount max.	1.80 m
Windrow cross-section max.	3.60 m ²
Space utilisation	0.95 m ³ /m ²
Machine Efficiency Class A+	0.05 kWh/m ³
Grain size max.	200 mm
Passage width	3,000 mm
Clearance height	1,800 mm
Turnover capacity (depending on material) up to	1,500 m ³ /h
Rotor speed	0-170 1/min
Rotor diameter	1,000 mm
Travel speed up to	50 m/min

Working Position Dimensions

Length	3,590 mm
Width	3,930 mm
Height	2,230 mm

Transport position dimensions

Length	3,930 mm
Width	2,470 mm
Height	2,230 mm
Weight approx.	8,000 kg